

Dimensions				Basical load		Speed ratings		Designation	Weight
d	D	B	r1,r2 min	dyn. Cr	stat. C0r	grease	oil		
mm				kN		min-1		-	kg
10	30	14	0,6	9,20	5,20	18000	22000	4200 B.TN	0,049
12	32	14	0,6	10,60	6,20	17000	20000	4201 B.TN	0,053
15	35	14	0,6	11,90	7,50	14000	17000	4202 B.TN	0,059
15	42	17	1,0	14,80	9,50	12000	15000	4302 B.TN	0,12
17	40	16	0,6	14,80	9,50	12000	15000	4203 B.TN	0,09
17	47	19	1,0	19,50	13,50	10000	13000	4303 B.TN	0,16
20	47	18	1,0	17,80	12,50	10000	13000	4204 B.TN	0,14
20	52	21	1,1	23,40	16,00	9500	12000	4304 B.TN	0,21
25	52	18	1,0	19,00	14,50	9000	11000	4205 B.TN	0,16
25	62	24	1,1	31,90	22,50	8500	10000	4305 B.TN	0,34
30	62	20	1,0	26,00	20,50	8000	9500	4206 B.TN	0,26
30	72	27	1,1	41,20	30,00	7000	8500	4306 B.TN	0,5
35	72	23	1,1	35,10	28,50	6700	8000	4207 B.TN	0,4
35	80	31	1,5	50,50	38,00	6300	7500	4307 B.TN	0,69
40	80	23	1,1	37,05	32,50	6000	7000	4208 B.TN	0,5
40	90	33	1,5	55,70	45,00	5600	6700	4308 B.TN	0,95
45	85	23	1,1	39,00	36,00	5600	6700	4209 B.TN	0,54
45	100	36	1,5	68,50	56,00	5000	6000	4309 B.TN	1,25
50	90	23	1,1	40,50	40,00	5000	6000	4210 B.TN	0,58
50	110	40	2,0	815,00	70,00	4500	5300	4310 B.TN	1,7
55	100	25	15,0	45,00	44,00	4800	5600	4211 B.TN	0,8
55	120	43	2,0	975,00	83,00	4300	5000	4311 B.TN	2,15
60	110	28	15,0	57,00	55,00	4500	5300	4212 B.TN	1,1
60	130	46	21,0	112,00	98,00	3800	4500	4312 B.TN	2,65
65	120	31	15,0	675,00	67,00	4000	4800	4213 B.TN	1,45
70	125	31	15,0	70,00	735,00	3600	4300	4214 B.TN	1,5
75	130	31	15,0	725,00	80,00	3400	4000	4215 B.TN	1,6
80	140	33	2,0	805,00	90,00	3200	3800	4216 B.TN	2
85	150	36	2,0	936,00	102,00	3000	3600	4217 B.TN	2,55
90	160	40	2,0	112,00	122,00	2800	3400	4218 B.TN	3,2